

RT60 SPRAY PLUS

SPRAY SYSTEM DUST SUPPRESSANT

- > The most effective wetting technology available
- > Saves water
- > Economical
- > Fast results
- > Easily applied
- > Environmentally safe



DESCRIPTION

RT60 SPRAY PLUS is a highly concentrated wetting agent with outstanding wetting performance characteristics. Added to water at ultra low dosage rates, RT60 SPRAY PLUS changes the characteristics of water allowing it to penetrate, saturate and spread much faster than plain water.

RT60 SPRAY PLUS can be used for the following applications:

- Increasing DEM (Dust Extinction Moisture) levels – fast!
- To improve the dust suppression capabilities of spray nozzle systems
- To reduce the amount of water added to ore during transfer
- To improve the effectiveness of water when used for dust control
- Allows larger water particles to capture smaller dust particles
- To increase water flow through minerals and ore

APPLICATION

The addition of RT60 SPRAY PLUS into any water flow is achieved through injection using a small dosing pump such as a “Dosatron” which allows for very accurate dosing of the product at the recommended low dosage rates. When RT60 SPRAY PLUS is added to the water used to suppress dust through spray nozzle systems, it will reduce the build up of scale (calcium) and other forms of grime to pipe work and nozzles.

RT60 SPRAY PLUS can also be applied via other general spray equipment.

Dosage rates vary between 0.005% - 0.05%