

ROAD BINDER

HEAVY DUTY LONG TERM ROAD DUST SUPPRESSANT & STABILISER AID

BENEFITS

- One treatment controls road dust up to 3 months
- After treatment no further watering is required
- Physically 'binds' the road material together
- Does not require special application equipment
- Improves the road running surface, reducing maintenance
- Non-hazardous and eco-friendly

DESCRIPTION

Road Binder is a unique water dispersion of vinylic resins supplied as a viscous liquid. It is diluted into water carts and sprayed onto or blended into roads, airstrips and hardstand areas etc where watering programs cannot be implemented to control dust emissions.

- Physically binds particles together and stabilises road materials
- Forms a mechanically high resistant and elastic coating
- Eliminates continual watering programs

APPLICATION - SURFACE

For a topical treatment, ROAD BINDER is dosed at 250ml per m² per pass. It is recommended that two passes be conducted.

The first pass is diluted at 1:6 applied at 1.75L per m². The second pass diluted at 1:4 in water applied at 1.25L per m².

Dosage/applications recommended are dependant on the traffic volumes, type of vehicles and duration of dust suppression requirements.

APPLICATION – BLENDED

Dose 250ml of **ROAD BINDER** concentrate per m² and dilute into compaction water at 1:6 applied at 1.75L per m² up to a depth of 150mm, then blend and compact.

HEALTH, SAFETY, ENVIRONMENT AND THE COMMUNITY (HSEC)

RST strives, through a process of continuous improvement, to fully integrate health, safety, environmental and community (HSEC) consciousness into all aspects of its activities

For more information and to obtain the Material Safety Data Sheet please contact RST.