

ASBESTOGUARD

ASBESTOS BINDING AGENT FOR CONSTRUCTION & DEMOLITION

- > Requires only one application
- > Dilutes in water allowing for varying binding strengths and longevity requirements
- > Cross-linking polymer once dry will not soften or wash off
- > Mixed with RT60 Super Wetter for hard to wet surfaces and materials
- > Easily applied through any watering system
- > Environmentally friendly
- > UV and rain tolerant
- > Marking dye can be added to monitor application areas and strengths



DESCRIPTION

ASBESTOGUARD is a specialty polymer emulsion developed by RST. It is an asbestos-binding agent used during construction and demolition involving any movement of asbestos contaminated material.

ASBESTOGUARD is diluted in water (1:20) and sprayed onto any asbestos contaminated material for long-term results. ASBESTOGUARD works on all material types.

Main areas of application include:

- Construction projects including asbestos roofs
- Asbestos contaminated building demolition
- Contaminated earthworks
- Asbestos contaminated rail and truck loads
- All exposed asbestos contaminated materials and areas

APPLICATION

When spraying on hard surfaces (such as building frames, asbestos sheeting), the surface must be thoroughly wetted and covered by ASBESTOGUARD.

Excellent results for contaminated earthworks have been achieved applying ASBESTOGUARD diluted at 1:20 and applied at 1 litre per m² of material.

If the material to be treated is very dry and water repelling, we recommend the addition of RT60 Super Wetter at a dilution rate of 1:1000 in the ASBESTOGUARD solution.

For more information and to obtain the Material Safety Data Sheet please contact RST.